


Adjustable Air Terminal Adapter

The adjustable air terminal adapter adjusts at 180 degree range. Also available in tin plated.


- 2401** 3/8" I.D. top to 3/8" I.D. cast bronze swivel **WT 5.1 oz (144.6 g)**
- 2403** 1/2" I.D. top to 1/2" I.D. cast bronze swivel **WT 5.6 oz (158.8 g)**
- 2404** 3/8" I.D. top to 5/8" O.D. cast bronze swivel **WT 5.2 oz (147.4 g)**
- 2405** 1/2" I.D. top to 5/8" O.D. cast bronze swivel **WT 5.3 oz (150.2 g)**
- 2406** 5/8" I.D. top to 5/8" O.D. cast bronze swivel **WT 5.3 oz (150.2 g)**
- 2407** 1/2" I.D. top to 5/8" I.D. cast bronze swivel **WT 5.3 oz (150.3 g)**
- 2408** 3/8" I.D. top to 5/8" I.D. cast bronze swivel **WT 5.2 oz (147.4 g)**
- 2403A** 1/2" I.D. top to 1/2" I.D. cast aluminum swivel **WT 2.6 oz (73.7)**
- 2405A** 1/2" I.D. top to 5/8" O.D. cast aluminum swivel **WT 3.1 oz (87.9 g)**
- 2406A** 5/8" I.D. top to 5/8" O.D. cast aluminum swivel **WT 1.9 oz (53.9 g)**
- 2407A** 1/2" I.D. top to 5/8" I.D. cast aluminum swivel **WT 1.9 oz (53.9 g)**



Note: Please call ALLTEC Corporation for orders requiring different configurations and sizes.


Air Terminal Adapter

- 2411** Cast bronze adapter for 3/8" air terminal with 3/8" I.D. threads **WT 2.4 oz (68.0 g)**
- 2412** Cast bronze adapter for 3/8" air terminal with 1/2" I.D. threads **WT 2.2 oz (62.4 g)**
- 2413** Cast bronze adapter for 3/8" air terminal with 5/8" I.D. threads **WT 2.4 oz (68.0 g)**
- 2414** Cast bronze adapter for 1/2" air terminal with 1/2" I.D. threads **WT 2.2 oz (62.4 g)**
- 2414A** Cast aluminum adapter for 1/2" air terminal with 1/2" I.D. threads **WT 2.2 oz (62.4 g)**
- 2415** Cast bronze adapter for 1/2" air terminal with 5/8" I.D. threads **WT 2.4 oz (68.0 g)**
- 2415A** Cast aluminum adapter for 1/2" air terminal with 5/8" I.D. threads **WT 1.0 oz (28.3 g)**



Concealed Air Terminal Adapter

- 2423** Cast bronze adapter for 3/8" I.D. thread at top and 3/8" I.D. thread at the bottom **WT 2.2 oz (62.4 g)**
- 2424** Cast bronze adapter for 1/2" I.D. thread at top and 3/8" I.D. thread at the bottom **WT 2.4 oz (68.0 g)**
- 2425** Cast bronze adapter for 5/8" O.D. thread at top and 1/2" I.D. thread at the bottom **WT 2.2 oz (62.4 g)**
- 2425A** Cast aluminum adapter for 5/8" O.D. thread at top and 1/2" I.D. thread at the bottom **WT 1.0 oz (28.3 g)**



Threaded Couplings

- 2433** Cast bronze coupler with 3/8" I.D. threads **WT 1.3 oz (368.5 g)**
- 2435** Cast bronze coupler with 1/2" I.D. threads **WT 1.5 oz (42.5 g)**
- 2435A** Cast aluminum coupler with 1/2" I.D. threads **WT 1.0 oz (28.3 g)**
- 2437** Cast bronze coupler with 5/8" I.D. threads **WT 3.5 oz (99.2 g)**
- 2437A** Cast aluminum coupler with 5/8" I.D. threads **WT 1.0 oz (28.2 g)**

