

## Air Terminal Brace

### Tripod Air Terminal Brace

This mechanical fastened brace is used where conditions require additional support for long air terminals. The tripod brace is made of 1/4" special tempered copper or aluminum rod.

- 2518** 18" Copper Tripod **WT 1.00 lbs (0.45 kg)**
- 2524** 24" Copper Tripod **WT 1.50 lbs (0.68 kg)**
- 2536** 36" Copper Tripod **WT 2.00 lbs (0.90 kg)**
- 2548** 48" Copper Tripod **WT 2.50 lbs (1.1 kg)**

- 2618A** 18" Aluminum Tripod **WT 1.00 lbs (0.45 kg)**
- 2624A** 24" Aluminum Tripod **WT 1.25 lbs (0.56 kg)**
- 2636A** 36" Aluminum Tripod **WT 1.50 lbs (0.68 kg)**
- 2648A** 48" Aluminum Tripod **WT 1.75 lbs (0.79 kg)**

### Adhesive Tripod Air Terminal Brace

The adhesive fastened brace is used where conditions require additional support for long air terminals without roof penetration. The tripod brace is made of 1/4" special tempered copper or aluminum rod.

- 2718** 18" Copper Tripod **WT 1.00 lbs (0.45 kg)**
- 2724** 24" Copper Tripod **WT 1.50 lbs (0.68 kg)**
- 2736** 36" Copper Tripod **WT 2.00 lbs (0.90 kg)**
- 2748** 48" Copper Tripod **WT 2.50 lbs (1.1 kg)**

- 2818A** 18" Aluminum Tripod **WT 1.00 lbs (0.45 kg)**
- 2824A** 24" Aluminum Tripod **WT 1.25 lbs (0.56 kg)**
- 2836A** 36" Aluminum Tripod **WT 1.50 lbs (0.68 kg)**
- 2848A** 48" Aluminum Tripod **WT 1.75 lbs (0.79 kg)**

