

## ***Flat Copper Strap Conductors***

**All Copper Strap is sold in 100' rolls**

Part #	Width	Thick	GA.	Length	Weight/Roll
CS1016	5/8"	.064"	14	100'	15.4 (6.9 kg)
CS1018	5/8"	.125"	8	100'	30.2 (13.7 kg)
CS1114	1"	.032"	20	100'	12.4 (5.6 kg)
CS1116	1"	.064"	14	100'	24.8 (11.2 kg)
CS1118	1"	.125"	8	100'	48.3 (21.9 kg)
CS1212	2"	.016"	26	100'	12.4 (5.6 kg)
CS1214	2"	.032"	20	100'	24.8 (11.2 kg)
CS1216	2"	.064"	14	100'	49.6 (22.5 kg)
CS1412	4"	.016"	26	100'	24.8 (11.2 kg)
CS1414	4"	.032"	20	100'	49.6 (22.5 kg)
CS1612	6"	.016"	26	100'	37.1 (16.8 kg)

Other custom sizes available by special order.

## ***Lightning Strike Counter***

### **ASC-6X**

Counter displays the number of lightning strikes that have hit a system. The counter is for use on tower legs or other down conductors such as cables. It connects to two points on the conductor, spaced at least 8 feet apart, using #14 or larger wire (not included). Features include weather proof enclosure, internal protection, and six digit readout. Mounts to any flat surface. The Strike Counter ASC-6X is for outdoor use.

**WT 4.0 oz (113.4 g)**

