



Nails

- 6221** 4 penny copper nail **WT 182 pc/lb (83 pc/kg)**
6221A 4 penny aluminum nail **WT 585 pc/lb (266 pc/kg)**
6221S 4 penny stainless steel nail **WT 209 pc/lb (95 pc/kg)**

**Adhesive**

- 6231** UV-6800 is a self-leveling, multi purpose adhesive. It adheres to aluminum, steel, glass, fiberglass, concrete, PVC, and neoprene. UV-6800 has a tensile strength of 2,900 p.s.i. and a shear adhesion range from 400 to 600 p.s.i. Clear adhesive. **WT 14.3 oz (405.4 g)**



- 6233** NP1™ is a ready to use polyurethane sealant. It adheres to most metal, wood, poly-membrane, and concrete surfaces. NP1™ has a 350 p.s.i. tensile strength. Black adhesive. **WT 14.6 oz (413.9 g)**

Hex Head Machine Bolts

- 6301** 1/4" – 20 X 1/2" stainless steel hex head bolts
WT 12.46 lbs/M (5.65 kg/M)
- 6303** 1/4" – 20 X 3/4" stainless steel hex head bolts
WT 14.80 lbs/M (6.71 kg/M)
- 6305** 1/4" – 20 X 1" stainless steel hex head bolts
WT 17.77 lbs/M (8.03 kg/M)
- 6307** 1/4" – 20 X 1-1/4" stainless steel hex head bolts
WT 19.51 lbs/M (8.84 kg/M)
- 6309** 1/4" – 20 X 1-1/2" stainless steel hex head bolts **WT 22.23 lbs/M (10.08 kg/M)**
- 6311** 5/16" – 18 X 3/4" stainless steel hex head bolts **WT 24.00 lbs/M (10.88 kg/M)**
- 6313** 5/16" – 18 X 1" stainless steel hex head bolts **WT 28.20 lbs/M (12.79 kg/M)**
- 6315** 5/16" – 18 X 1-1/2" stainless steel hex head bolts **WT 36.50 lbs/M (16.56 kg/M)**
- 6317** 5/16" – 18 X 1-3/4" stainless steel hex head bolts **WT 43.90 lbs/M (19.73 kg/M)**
- 6319** 5/16" – 18 X 2" stainless steel hex head bolts **WT 44.80 lbs/M (20.32 kg/M)**
- 6320** 3/8" – 16 X 1/2" stainless steel hex head bolts **WT 37.00 lbs/M 16.78 kg/M)**
- 6321** 3/8" – 16 X 3/4" stainless steel hex head bolts **WT 42.00 lbs/M (19.05 kg/M)**
- 6323** 3/8" – 16 X 1" stainless steel hex head bolts **WT 47.70 lbs/M (21.63 kg/M)**
- 6325** 3/8" – 16 X 1-1/2" stainless steel hex head bolts **WT 55.80 lbs/M (25.31 kg/M)**
- 6327** 3/8" – 16 X 2" stainless steel hex head bolts **WT 67.60 lbs/M (30.66 kg/M)**
- 6329** 1/2" – 13 X 3/4" stainless steel hex head bolts **WT 7.28 lbs/C (3.30 kg/C)**
- 6331** 1/2" – 13 X 1" stainless steel hex head bolts **WT 8.36 lbs/C (3.80 kg/C)**
- 6333** 1/2" – 13 X 1-1/2" stainless steel hex head bolts **WT 10.63 lbs/C (4.82 kg/C)**
- 6335** 1/2" – 13 X 2" stainless steel hex head bolts **WT 13.33 lbs/C (6.05 kg/C)**

