


TYPE "K"

Copper Split Bolts

For Use With Copper To Copper Connectors

- For copper to copper connections.
- Bolt and nut of high strength corrosion resistant bronze alloy.
- Tested and listed to UL 486A requirements.
- UL Listed and CSA Certified for copper conductor only.



PART NUMBER	RANGE OF EQUAL MAIN & TAP CONDUCTORS	PCS/CTN	WT/100	MINIMUM TAP WITH ONE MAXIMUM MAIN
AK-10	10 STRAND- 12 SOLID	100	2	14 SOLID
AK-8	8 STRAND – 10 SOLID	100	3	14 SOLID
AK-6	6 SOLID – 8 SOLID	100	5.5	14 SOLID
AK-4	4 SOLID – 8 SOLID	50	7	14 SOLID
AK-3	3 SOLID – 8 SOLID	50	9	14 SOLID
AK-2	2 SOLID – 6 SOLID	50	9.5	14 SOLID
AK-1	2 STRAND – 6 SOLID	50	15	14 SOLID
AK-1/0	1/0 STRAND – 4 SOLID	25	19	14 SOLID
AK-2/0	2/0 STRAND – 2 SOLID	25	30	14 SOLID
AK-3/0	3/0 STRAND – 2 SOLID	20	34	14 SOLID
AK-4/0	4/0 STRAND – 2 SOLID	10	37	6 SOLID
AK-250	250 KCMIL – 1 STRAND	10	35	8 SOLID
AK-350	350 – 250 KCMIL	3	77	1/0 STRAND
AK-500	500 – 400 KCMIL	3	90	2/0 STRAND
AK-750	750 – 600 KCMIL	1	195	4/0 STRAND
AK-1000	1000 – 800 KCMIL	1	280	4/0 STRAND